



JXM-A series

Main specification

- ◆ The capacity up to 500 LPH
- ◆ The maximum pressure up to 12 bar
- ◆ Measuring accuracy reaches to +/-1%
- ◆ Temperatures of liquid shall be between -10°C~40°C
- ◆ Max.Suct: 2 m
- ◆ Motor: Standard 220V/380V, 50Hz

Main features

- ◆ Mechanical Actuated Diaphragm
- ◆ Changeable eccentric drive
- ◆ Power-off seal, no leakage, with security delivery
- ◆ Small size in simple structure

Control

- ◆ Manual adjustment of the stroke
- ◆ Stroke actuator
- ◆ Digital controller

Others

- ◆ It can be used to transport the goods which is high-viscosity, corrosive or dangerous
- ◆ Diaphragm rupture detection system (Double diaphragms)



Model	Capacity (LPH)		Max. Pressure (Bar)	Dia. plunger (mm)	Stroke (mm)	Speed (min-1)	Motor power (KW)	Weight (KGS)	
	50Hz	60Hz							
JXM-A2.25/1.2	2.25	2.7	12	36	36	1.2	0.37KW	20	
JXM-A 4.5/1.2	4.5	5.4		72					
JXM-A 9/1.2	9	10.8		144					
JXM-A 22/1.2	22	26.4		72					
JXM-A 44/1	44	52.8	10	144	45	4			
JXM-A 85/1	85	102		72					
JXM-A 120/0.7	120	144	7	72	110/70	6			
JXM-A 170/0.7	170	204		144		8			
JXM-A 240/0.7	240	288		144		6			
JXM-A 315/0.5	315	378		144		8			
JXM-A 400/0.5	400	480	5	144	110/80	8			0.55 KW
JXM-A 500/0.5	500	600		180					

